

## Technické údaje hliníkových roliet

MAXIMÁLNA VÝŠKA ROLETY V DANEJ KAZETE - PREDOKENNÉ ROLETY																		
LAMELA / KAZETA (CM)	137 mm		165 mm				180 mm				205 mm		250 mm		300 mm		350 mm	
	štandard		štandard		kombi		štandard		kombi		štandard		štandard		štandard		štandard	
hriadeľ (mm)	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 60	ø 70	ø 60	ø 70	ø 60	ø 70
37 mm plast	156	145	235	222	180	161	284	270	225	200	430	419	-	-	-	-	-	-
39 mm hliník	155	144	239	228	180	161	295	279	225	200	432	403	-	-	-	-	-	-
45 mm hliník	-	84	-	160	-	123	-	212	-	166	-	265	-	-	-	-	-	-
55 mm hliník	-	-	-	94	-	-	-	136	-	-	-	195	312	320	460	480	500	500
77 mm hliník	-	-	-	-	-	-	-	-	-	-	-	-	194	194	328	328	477	477

MAXIMÁLNA VÝŠKA ROLETY V DANEJ KAZETE - NADOKENNÉ ROLETY												
LAMELA / TOK (CM)	210 x 210 mm				210 x 255 mm				255 x 250 mm			
	štandard		kombi		štandard		kombi		štandard		combi	
tengely (mm)	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60	ø 40	ø 60
37 mm plast	290	270	200	185	290	270	200	185	325	310	200	185
39 mm hliník	295	275	210	200	295	275	210	200	325	310	210	200
45 mm hliník	-	245	-	-	-	245	-	-	-	245	-	-

vodiaca koľajnica : štandard 60 x 33 mm, combi 60 x 52 mm

**HODNOTY PRENOSU TEPLA**

W / M <sup>2</sup> K	Predokenné hliníkové rolety	Hliníkové garážové brány	Nadokenné plastové rolety
		Lamela : PA 37,PA 39, PA 45,PA 55	Lamela : PA 77
U hodnoty prenosu tepla	4,065	2,016	0,680

**ROZMERY VODIACICH KOĽAJNÍC**

LAMELA,KAZETA (MM)	137 mm		165 mm		180 mm		205 mm	250 mm	300 mm	350 mm
	štandard	štandard	kombi	štandard	kombi	štandard	štandard	štandard	štandard	
37 mm plast	53x22	53x22	53x44	53x22	53x44	53x22	-	-	-	-
39 mm hliník	53x22 68x22	53x22 68x22	53x40	53x22 68x22	53x40	53x22 68x22	-	-	-	-
45 mm hliník	53x22 68x22	53x22 68x22	53x40	53x22 68x22	53x40	53x22 68x22	-	-	-	-
55 mm hliník	-	66x27	-	66x27	-	66x27	75 x 27	75 x 27	75 x 27	75 x 27
77 mm hliník	-	-	-	-	-	-	89x34	89x34	89x34 110x34	89x34 110x34

**HMOTNOSŤ LAMIEL**

KG/M <sup>2</sup>	37 mm plast	39 mm hliník	45 mm hliník	52 mm hliník	55 mm hliník	77 mm hliník
hmotnosť na m <sup>2</sup>	2,91	2,54	2,8	3,00	3,40	4,80

**SOMFY MOTORY PRE ROLETOVÉ BRÁNY**ÚDAJE V TABUĽKE PLATIA PRI POUŽITÍ SW 60, SW 70 HRIADEĽA, 77 MM LAMELA, 6KG/M<sup>2</sup>

VÝŠKA	ŠÍRKA (M)												
	1	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5	7
1 m	6	6	8	10	15	15	20	20	20	25	25	30	30
1,5 m	8	10	15	20	20	25	30	30	35	35	40	45	45
2 m	10	15	20	25	30	35	40	45	50	55	60	70	70
2,5 m	15	20	30	35	40	50	55	60	70	80	80	85	100
3 m	20	30	35	45	55	70	70	70	80	80	100	100	120
3,5 m	25	35	45	55	70	80	80	80	100	100	120	120	
4 m	35	50	70	80	100	120	120	120					
4,5 m	40	55	80	100	120								
5 m	45	70	85	120									
5,5 m	50	80	100	120									
6 m	55	80	120										
6,5 m	60	80	120										
7 m	70	85	120										

Uvedené údaje sú v Nm